

-----  
M A T E R I A L   S A F E T Y   D A T A   S H E E T  
-----

=====

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

=====

PRODUCT NAME : CAULK 100XT COMP. B  
IDENTIFICATION NUMBER: MSDCLK100XTB PREPARE/REVISED: 08/07/06  
PRODUCT USE/CLASS : FLUROELASTOMER

SUPPLIER:	MANUFACTURER:
Dudick, Inc.	Dudick, Inc.
1818 Miller Parkway	1818 Miller Parkway
Streetsboro, Ohio 44241	Streetsboro, Ohio 44241
CHEM-TEL: 800-255-3924	CHEM-TEL: 800-255-3924
24 HOURS A DAY	24 HOURS A DAY

PREPARER: DUDICK, INC., PHONE: 800-322-1970

=====

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

=====

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % LESS THAN
01	ETHANOL	64-17-5	55.0 %
02	KETIMINE	25707-70-4	35.0 %
03	METHANOL	67-56-1	5.0 %
04	METHYL ISOBUTYL KETONE	108-10-1	1.0 %

ITEM	EXPOSURE LIMITS					
	ACGIH		OSHA		COMPANY	
TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING	TLV-TWA	SKIN	
01	1000 PPM	NO INFO	NO INFO	NO INFO	NE	NO
02	NO INFO	NO INFO	NO INFO	NO INFO	NE	YES
03	200PPM SKIN	250PPM	200PPM SKIN	NO INFO	NE	YES
04	50PPM	75PPM	50PPM	75PPM STEL	NE	YES

(See Section 16 for abbreviation legend)

=====

SECTION 3 - HAZARDS IDENTIFICATION

=====

\*\*\* EMERGENCY OVERVIEW \*\*\*: EYE AND SKIN IRRITANT. HARMFUL IF SWALLOWED.  
RESPIRATORY TRACT IRRITANT.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: MODERATE EYE IRRITANT.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: REPEATED EXPOSURE MAY CAUSE DRYING  
AND FLAKING OF THE SKIN. MAY CAUSE SKIN IRRITATION.

(Continued on Page 2)

=====

=====  
SECTION 3 - HAZARDS IDENTIFICATION  
=====

EFFECTS OF OVEREXPOSURE - INHALATION: MAY CAUSE SLURRED SPEECH, DIZZINESS, GIDDINESS, AND POSSIBLE LOSS OF CONSCIOUSNESS.

EFFECTS OF OVEREXPOSURE - INGESTION: INGESTION MAY CAUSE NAUSEA, CRAMPS, VOMITING, AND DIARRHEA. ASPIRATION HAZARD. PRODUCT MAY ENTER THE LUNGS DURING SWALLOWING AND CAUSE LUNG DAMAGE.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: PREEXISTING SKIN OR LUNG INJURIES MAY INCREASE THE CHANCE OF DEVELOPING ALLERGY SYMPTOMS FROM EXPOSURE TO THIS PRODUCT. MAY CAUSE SKIN SENSITIZATION. CHRONIC LONG TERM OVEREXPOSURE OR INTENTIONAL ABUSE, MISUSE, OR OTHER MASSIVE EXPOSURE TO SOLVENT CONTAINING PRODUCTS MAY CAUSE MULTIPLE ORGAN DAMAGE AND/OR DEATH. MALE RATS EXPOSED TO METHYL ISOBUTYL KETONE VAPORS (1000PPM) FOR 90 DAYS SHOWED EVIDENCE OF KIDNEY DAMAGE. THE SIGNIFICANCE OF THIS EFFECT TO MAN IS UNKNOWN.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT SKIN ABSORPTION INHALATION  
INGESTION EYE CONTACT

=====  
SECTION 4 - FIRST AID MEASURES  
=====

FIRST AID - EYE CONTACT: HOLD OPEN EYE LIDS AND FLUSH WITH COPIOUS AMOUNTS OF FLOWING WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION.

FIRST AID - SKIN CONTACT: WASH AFFECTED AREAS THOROUGHLY WITH SOAP AND WATER. IF SYMPTOMS PERSIST, SEEK MEDICAL ATTENTION. REMOVE CONTAMINATED CLOTHING AND WASH THOROUGHLY BEFORE REUSE.

FIRST AID - INHALATION: REMOVE VICTIM TO FRESH AIR. IF VICTIM IS NOT BREATHING, ARTIFICIAL RESPIRATION SHOULD BE ADMINISTERED BY QUALIFIED PERSONNEL. SUPPLEMENTAL OXYGEN MAY BE INDICATED. CALL A PHYSICIAN.

FIRST AID - INGESTION: IF SWALLOWED, CALL A PHYSICIAN IMMEDIATELY. REMOVE CONTENTS OF STOMACH ONLY AS DIRECTED BY MEDICAL PERSONNEL. GIVE VICTIM PLENTY OF WATER TO DRINK IF CONSCIOUS.

=====  
SECTION 5 - FIRE FIGHTING MEASURES  
=====

FLASH POINT: 55 F LOWER EXPLOSIVE LIMIT: 1.2 %  
(TAGLIABUE CLOSED CUP) UPPER EXPLOSIVE LIMIT: 36.5 %

AUTOIGNITION TEMPERATURE: NE

EXTINGUISHING MEDIA: ALCOHOL FOAM CO2 DRY CHEMICAL FOAM WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL A LONG DISTANCE AND FLASH BACK. TOXIC FUMES MAY BE PRODUCED IF THIS PRODUCT IS INVOLVED IN A FIRE.

SPECIAL FIRE FIGHTING PROCEDURES: EVACUATE AREA. WATER MAY BE INEFFECTIVE

(Continued on Page 3)

=====

=====|  
| SECTION 5 - FIRE FIGHTING MEASURES |  
=====|

BUT MAY BE USED TO COOL FIRE EXPOSED CONTAINERS. FIGHT FIRE FROM A SAFE DISTANCE. WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING.

=====|  
| SECTION 6 - ACCIDENTAL RELEASE MEASURES |  
=====|

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: ABSORB EXCESS WITH SAND, EARTH, OR VERMICULITE. SCRAPE UP AND PLACE IN SUITABLE CONTAINER FOR DISPOSAL. WEAR ALL APPROPRIATE SAFETY EQUIPMENT WHILE HANDLING SPILLS. USE NON-SPARKING TOOLS.

=====|  
| SECTION 7 - HANDLING AND STORAGE |  
=====|

HANDLING: AVOID CONTACT WITH EYES AND SKIN. AVOID BREATHING VAPORS. FOR INDUSTRIAL USE ONLY. WEAR APPROPRIATE SAFETY EQUIPMENT WHEN HANDLING.

STORAGE: DO NOT STORE NEAR INCOMPATIBLES. DO NOT STORE NEAR EXCESSIVE HEAT OR NEAR SOURCES OF IGNITION. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE.

=====|  
| SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION |  
=====|

ENGINEERING CONTROLS: GENERAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO MINIMIZE VAPOR CONCENTRATIONS. LOCAL EXHAUST MAY BE REQUIRED.

RESPIRATORY PROTECTION: WEAR A PROPERLY FITTED NIOSH APPROVED RESPIRATOR WHEN THE TLV IS EXCEEDED.

SKIN PROTECTION: IMPERVIOUS RUBBER OR NEOPRENE TYPE. CONSULT GLOVE MANUFACTURER FOR RECOMMENDATIONS.

EYE PROTECTION: USE SPLASH-PROOF GOGGLES OR FACE SHIELD WHEN EYE CONTACT MAY OCCUR.

OTHER PROTECTIVE EQUIPMENT: CLEAN, FULL BODY COVERING TO MINIMIZE SKIN CONTACT WITH MATERIAL. AN EYEWASH STATION AND SAFETY SHOWER IS RECOMMENDED NEAR WORK AREA.

HYGIENIC PRACTICES: SMOKING OR EATING IN THE WORK AREA SHOULD NOT BE PERMITTED. WASH THOROUGHLY AFTER HANDLING MATERIAL.

=====|  
| SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES |  
=====|

BOILING RANGE : 148 - 241 F VAPOR DENSITY : Is heavier than air  
ODOR : SOLVENT ODOR THRESHOLD : NE

(Continued on Page 4)

=====



=====  
SECTION 14 - TRANSPORTATION INFORMATION  
=====

=====  
SECTION 15 - REGULATORY INFORMATION  
=====

THE FOLLOWING COMPONENTS ARE NOT SUBJECT TO REPORTING IN SECTION 2:

----- CHEMICAL NAME -----	CAS NUMBER	WT/WT % IS LESS THAN
ACTIVE SOLIDS	NO INFO	20.0 %

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD    CHRONIC HEALTH HAZARD    FIRE HAZARD

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME -----	CAS NUMBER	WT/WT % IS LESS THAN
METHANOL	67-56-1	5.0 %
METHYL ISOBUTYL KETONE	108-10-1	1.0 %

TOXIC SUBSTANCES CONTROL ACT:

The chemical substances in this product are on the TSCA Section 8 Inventory.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

----- CHEMICAL NAME -----	CAS NUMBER
No information is available.	

U.S. STATE REGULATIONS: AS FOLLOWS -

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product:

----- CHEMICAL NAME -----	CAS NUMBER
ACTIVE SOLIDS	NO INFO

(Continued on Page 6)

=====

=====|  
| SECTION 15 - REGULATORY INFORMATION |  
|=====|

PENNSYLVANIA RIGHT-TO-KNOW:

The following non-hazardous ingredients are present in the product at greater than 3%:

----- CHEMICAL NAME -----	CAS NUMBER
ACTIVE SOLIDS	NO INFO

CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

----- CHEMICAL NAME -----	CAS NUMBER
No Proposition 65 chemicals exist in this product.	

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: B

=====|  
| SECTION 16 - OTHER INFORMATION |  
|=====|

HMIS RATINGS - HEALTH: 3      FLAMMABILITY: 3      REACTIVITY: 1

VOLATILE ORGANIC COMPOUNDS (VOCS): 4.77 lbs/gal,    572 grams/ltr

LEGEND: N.A. - Not Applicable, N.E. - Not Established,  
N.D. - Not Determined

=====

The information contained on this MSDS has been compiled from information obtained from raw material suppliers and is believed to be accurate. It is the responsibility of the user to comply with all Federal, State and Local Regulations.

=====

<END OF MSDS>