

-----  
M A T E R I A L   S A F E T Y   D A T A   S H E E T  
-----

===== SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION =====

PRODUCT NAME : CAULK PSC COMP. A  
IDENTIFICATION NUMBER: CLKPSCGRYA0A PREPARE/REVISED: 08/07/06  
PRODUCT USE/CLASS : POLYSULFIDE CAULK

SUPPLIER: DUDICK, INC. MANUFACTURER: DUDICK, INC.  
1818 MILLER PARKWAY 1818 MILLER PARKWAY  
STREETSBORO, OHIO 44241 STREETSBORO, OHIO 44241

CHEM-TEL: 800-255-3924 CHEM-TEL: 800-255-3924  
24 HOURS A DAY 24 HOURS A DAY

PREPARER: DUDICK, INC., PHONE: 800-322-1970

===== SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS =====

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % LESS THAN
01	2,4,6-TRI(DIMETHYLAMINOMETHYL)PHENOL	MIXTURE	5.0 %
02	SILICON DIOXIDE (AMORPHOUS)	7631-86-9	5.0 %

ITEM	EXPOSURE LIMITS					
	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL-CEILING	COMPANY TLV-TWA	SKIN
01	5PPM	10PPM				YES
02	10mg/m3	NO INFO	6mg/m3	NO INFO	NE	NO

(See Section 16 for abbreviation legend)

===== SECTION 3 - HAZARDS IDENTIFICATION =====

\*\*\* EMERGENCY OVERVIEW \*\*\*: CAUTION!...MAY CAUSE EYE AND SKIN IRRITATION.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: MILD EYE IRRITANT.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: MODERATE SKIN IRRITANT.

EFFECTS OF OVEREXPOSURE - INHALATION: PRODUCT IS NOT EXPECTED TO BE A MAJOR INHALATION HAZARD. THIS PRODUCT HAS A DISAGREEABLE ODOR AND MAY PRODUCE SYMPTOMS AT LOW CONCENTRATIONS.

EFFECTS OF OVEREXPOSURE - INGESTION: THIS PRODUCT HAS A LOW ORDER ORAL TOXICITY.

(Continued on Page 2)

```

=====
|                                     |
|                               SECTION 3 - HAZARDS IDENTIFICATION          |
|                                     |
=====

```

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: PREEXISTING SKIN AND EYE DISORDERS MAY BE AGGRAVATED BY THIS PRODUCT.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT EYE CONTACT

```

=====
|                                     |
|                               SECTION 4 - FIRST AID MEASURES              |
|                                     |
=====

```

FIRST AID - EYE CONTACT: FLUSH EYES WITH FLOWING WATER UNTIL IRRITATION CEASES. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION.

FIRST AID - SKIN CONTACT: WASH AFFECTED AREAS THOROUGHLY WITH SOAP AND WATER. IF SYMPTOMS PERSIST, SEEK MEDICAL ATTENTION. REMOVE CONTAMINATED CLOTHING AND WASH THOROUGHLY BEFORE REUSE.

FIRST AID - INHALATION: REMOVE VICTIM TO FRESH AIR. IF VICTIM IS NOT BREATHING, ARTIFICIAL RESPIRATION SHOULD BE ADMINISTERED BY QUALIFIED PERSONNEL.

FIRST AID - INGESTION: IF SWALLOWED, CALL A PHYSICIAN IMMEDIATELY. REMOVE CONTENTS OF STOMACH ONLY AS DIRECTED BY MEDICAL PERSONNEL. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

```

=====
|                                     |
|                               SECTION 5 - FIRE FIGHTING MEASURES          |
|                                     |
=====

```

FLASH POINT: 201 F	LOWER EXPLOSIVE LIMIT: N.A.
(SETAFLASH CLOSED CUP)	UPPER EXPLOSIVE LIMIT: N.A.

AUTOIGNITION TEMPERATURE: NE

EXTINGUISHING MEDIA: ALCOHOL FOAM CO2 DRY CHEMICAL FOAM WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: TOXIC FUMES MAY BE PRODUCED IF THIS PRODUCT IS INVOLVED IN A FIRE.

SPECIAL FIREFIGHTING PROCEDURES: WATER MAY BE INEFFECTIVE BUT MAY BE USED TO COOL FIRE EXPOSED CONTAINERS. FIGHT FIRE FROM A SAFE DISTANCE. WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING.

```

=====
|                                     |
|                               SECTION 6 - ACCIDENTAL RELEASE MEASURES      |
|                                     |
=====

```

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: SCRAPE UP AND PLACE IN SUITABLE CONTAINER FOR DISPOSAL. WEAR ALL APPROPRIATE SAFETY EQUIPMENT WHILE HANDLING SPILLS.

=====

=====|  
SECTION 7 - HANDLING AND STORAGE  
=====|

HANDLING: AVOID CONTACT WITH EYES AND SKIN. FOR INDUSTRIAL USE ONLY.

STORAGE: DO NOT STORE NEAR EXCESSIVE HEAT OR NEAR SOURCES OF IGNITION.  
KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE.

=====|  
SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION  
=====|

ENGINEERING CONTROLS: GENERAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO  
MINIMIZE VAPOR CONCENTRATIONS. LOCAL EXHAUST MAY BE REQUIRED.

RESPIRATORY PROTECTION: NOT REQUIRED UNDER NORMAL CONDITIONS.

SKIN PROTECTION: CONSULT GLOVE MANUFACTURER FOR RECOMMENDATIONS.  
IMPERVIOUS GLOVES IF NEEDED TO PREVENT PROLONGED OR REPEATED CONTACT.

EYE PROTECTION: SAFETY GLASSES RECOMMENDED.

OTHER PROTECTIVE EQUIPMENT: CLEAN, FULL BODY COVERING TO MINIMIZE SKIN  
CONTACT WITH MATERIAL. AN EYEWASH STATION AND SAFETY SHOWER IS RECOMMENDED  
NEAR WORK AREA.

HYGIENIC PRACTICES: SMOKING OR EATING IN THE WORK AREA SHOULD NOT BE  
PERMITTED. WASH THOROUGHLY AFTER HANDLING MATERIAL.

=====|  
SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES  
=====|

BOILING RANGE	: N.A.	VAPOR DENSITY	: Is heavier than air
ODOR	: MERCAPTAN	ODOR THRESHOLD	: NE
APPEARANCE	: PASTE	EVAPORATION RATE	: Is slower than Ether
SOLUBILITY IN H2O	: INSOLUBLE		
FREEZE POINT	: NE	SPECIFIC GRAVITY	: 1.7
VAPOR PRESSURE	: NE	pH @ 0.0 %	: NE
PHYSICAL STATE	: PASTE	VISCOSITY	: NE
COEFFICIENT OF WATER/OIL DISTRIBUTION: NE			

(See Section 16 for abbreviation legend)

=====|  
SECTION 10 - STABILITY AND REACTIVITY  
=====|

CONDITIONS TO AVOID: NONE.

INCOMPATIBILITY: NONE KNOWN.

HAZARDOUS DECOMPOSITION PRODUCTS: BURNING WILL PRODUCE TOXIC FUMES.  
OXIDES OF CARBON. ALDEHYDES. OXIDES OF SULFUR.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

(Continued on Page 4)

=====

=====  
SECTION 11 - TOXICOLOGICAL PROPERTIES  
=====

No product or component toxicological information is available.

=====  
SECTION 12 - ECOLOGICAL INFORMATION  
=====

ECOLOGICAL INFORMATION: DO NOT CONTAMINATE PONDS, STREAMS, OR UNDERGROUND WATER SUPPLY. PREVENT FROM ENTERING SEWERS.

=====  
SECTION 13 - DISPOSAL CONSIDERATIONS  
=====

DISPOSAL METHOD: FOLLOW ALL RELEVANT LOCAL, STATE, AND FEDERAL REGULATIONS. DO NOT WELD,GRIND,OR USE CUTTING TORCHES ON EMPTY DRUMS.

=====  
SECTION 14 - TRANSPORTATION INFORMATION  
=====

DOT PROPER SHIPPING NAME: PUTTY COMPOUND NOI

DOT TECHNICAL NAME: NA

DOT HAZARD CLASS: NON-REGULATED      HAZARD SUBCLASS: NA

DOT UN/NA NUMBER: NA      PACKING GROUP: NA      RESP. GUIDE PAGE:

=====  
SECTION 15 - REGULATORY INFORMATION  
=====

THE FOLLOWING COMPONENTS ARE NOT SUBJECT TO REPORTING IN SECTION 2:

----- CHEMICAL NAME -----	CAS NUMBER	WT/WT % IS LESS THAN
POLYSULFIDE RESIN	UNKNOWN	60.0 %
SODIUM ALUMINUM SILICATE	UNKNOWN	35.0 %
IRON OXIDE	1309-37-1	1.0 %
GLYCERINE	56-81-5	1.0 %

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD

(Continued on Page 5)

=====

=====  
SECTION 15 - REGULATORY INFORMATION  
=====

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME -----      CAS NUMBER      WT/WT % IS LESS THAN  
No SARA Section 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

The chemical substances in this product are on the TSCA Section 8 Inventory.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

----- CHEMICAL NAME -----      CAS NUMBER  
No information is available.

U.S. STATE REGULATIONS: AS FOLLOWS -

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product:

----- CHEMICAL NAME -----	CAS NUMBER
POLYSULFIDE RESIN	UNKNOWN
SODIUM ALUMINUM SILICATE	UNKNOWN
IRON OXIDE	1309-37-1

PENNSYLVANIA RIGHT-TO-KNOW:

The following non-hazardous ingredients are present in the product at greater than 3%:

----- CHEMICAL NAME -----	CAS NUMBER
POLYSULFIDE RESIN	UNKNOWN
SODIUM ALUMINUM SILICATE	UNKNOWN

CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

----- CHEMICAL NAME -----      CAS NUMBER  
No Proposition 65 chemicals exist in this product.

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: D2

(Continued on Page 6)

=====

=====  
SECTION 16 - OTHER INFORMATION  
=====

HMIS RATINGS - HEALTH: 2      FLAMMABILITY: 1      REACTIVITY: 0

VOLATILE ORGANIC COMPOUNDS (VOCs): 0.07 lbs/gal,    8 grams/ltr

LEGEND: N.A. - Not Applicable, N.E. - Not Established,  
          N.D. - Not Determined

=====

The information contained on this MSDS has been compiled from information obtained from raw material suppliers and is believed to be accurate. It is the responsibility of the user to comply with all Federal, State and Local Regulations.

=====  
<END OF MSDS>