
M A T E R I A L S A F E T Y D A T A S H E E T

=====

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

=====

PRODUCT NAME : POLYMER ALLOY 1000 B
IDENTIFICATION NUMBER: PA1000B0000B PREPARE / REVISED: 08/07/06
PRODUCT USE/CLASS : EPOXY HARDENER

SUPPLIER: MANUFACTURER:
Dudick, Inc. Dudick, Inc.
1818 Miller Parkway 1818 Miller Parkway
Streetsboro, Ohio 44241 Streetsboro, Ohio 44241

CHEM-TEL: 800-255-3924 CHEM-TEL: 800-255-3924
24 HOURS A DAY 24 HOURS A DAY

PREPARER: DUDICK, INC PHONE: 800-322-1970

=====

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

=====

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % LESS THAN
01	ISOPHORONE DIAMINE	2855-13-2	25.0 %
02	BENZYL ALCOHOL	100-51-6	25.0 %
03	POLYPROPYLENEDIAMINE	9046-10-0	25.0 %
04	AMINE-EPOXY RESIN ADDUCT	UNKNOWN	20.0 %
05	PHENOLIC COMPOUND	UNKNOWN	20.0 %
06	TERTIARY AMINE	NO INFO	5.0 %

ITEM	EXPOSURE LIMITS					SKIN
	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL-CEILING	COMPANY TLV-TWA	
01	NE	NE	NE	NE	NE	YES
02	NO INFO	NO INFO	NO INFO	NO INFO	NE	NO
03	NO INFO	NO INFO	NO INFO	NO INFO	NE	NO
04	NO INFO	NO INFO	NO INFO	NO INFO	NE	YES
05	NO INFO	NO INFO	NO INFO	NO INFO	NE	YES
06	NE	NE	NE	NE	NE	YES

(See Section 16 for abbreviation legend)

=====

SECTION 3 - HAZARDS IDENTIFICATION

=====

*** EMERGENCY OVERVIEW ***: DANGER!---CAUSES BURNS. HARMFUL IF SWALLOWED.
DO NOT GET IN EYES, ON SKIN, OR CLOTHING. DO NOT BREATH VAPORS OR MISTS.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: EYE CONTACT MAY CAUSE SEVERE

(Continued on Page 2)

=====

```

=====
|                                     |
|                               SECTION 3 - HAZARDS IDENTIFICATION                               |
|                                     |
=====

```

IRRITATION WITH CORNEAL INJURY. MAY CAUSE BLINDNESS.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: PROLONGED EXPOSURE MAY CAUSE SKIN IRRITATION AND BURNS. SEVERE SKIN IRRITANT.

EFFECTS OF OVEREXPOSURE - INHALATION: VAPORS AND MISTS MAY BE CORROSIVE TO THE RESPIRATORY TRACT.

EFFECTS OF OVEREXPOSURE - INGESTION: INGESTION MAY CAUSE BURNS TO THE MOUTH, THROAT, AND ESOPHAGUS. INGESTION MAY CAUSE NAUSEA, CRAMPS, VOMITING, AND DIARRHEA.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: ALLERGIC REACTIONS MAY OCCUR IN SOME INDIVIDUALS. PREEXISTING SKIN AND EYE DISORDERS MAY BE AGGRAVATED BY THIS PRODUCT.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT SKIN ABSORPTION INHALATION INGESTION EYE CONTACT

```

=====
|                                     |
|                               SECTION 4 - FIRST AID MEASURES                               |
|                                     |
=====

```

FIRST AID - EYE CONTACT: HOLD OPEN EYE LIDS AND FLUSH WITH COPIOUS AMOUNTS OF FLOWING WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION.

FIRST AID - SKIN CONTACT: WASH AFFECTED AREAS THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND WASH THOROUGHLY BEFORE REUSE.

FIRST AID - INHALATION: REMOVE VICTIM TO FRESH AIR. IF VICTIM IS NOT BREATHING, ARTIFICIAL RESPIRATION SHOULD BE ADMINISTERED BY QUALIFIED PERSONNEL. SUPPLEMENTAL OXYGEN MAY BE INDICATED. CALL A PHYSICIAN.

FIRST AID - INGESTION: IF SWALLOWED, CALL A PHYSICIAN IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. GIVE VICTIM PLENTY OF WATER TO DRINK IF CONSCIOUS.

```

=====
|                                     |
|                               SECTION 5 - FIRE FIGHTING MEASURES                               |
|                                     |
=====

```

FLASH POINT: 201 F (SETAFLASH CLOSED CUP) LOWER EXPLOSIVE LIMIT: N.A. UPPER EXPLOSIVE LIMIT: N.A.

AUTOIGNITION TEMPERATURE: NE

EXTINGUISHING MEDIA: ALCOHOL FOAM CO2 DRY CHEMICAL FOAM WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: MAY PRODUCE TOXIC CARBON MONOXIDE AND NITROGEN OXIDES UPON COMBUSTION.

SPECIAL FIREFIGHTING PROCEDURES: EVACUATE AREA. WATER MAY BE INEFFECTIVE BUT MAY BE USED TO COOL FIRE EXPOSED CONTAINERS. FIGHT FIRE FROM A SAFE DISTANCE. WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE

(Continued on Page 3)

=====

=====|
SECTION 5 - FIRE FIGHTING MEASURES
=====|

CLOTHING.

=====|
SECTION 6 - ACCIDENTAL RELEASE MEASURES
=====|

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: DIKE AREA TO CONTAIN SPILLAGE. ABSORB EXCESS WITH SAND, EARTH, OR VERMICULITE. SCRAPE UP AND PLACE IN SUITABLE CONTAINER FOR DISPOSAL. WEAR ALL APPROPRIATE SAFETY EQUIPMENT WHILE HANDLING SPILLS.

=====|
SECTION 7 - HANDLING AND STORAGE
=====|

HANDLING: IF BODILY CONTACT OCCURS, REMOVE CONTAMINATED CLOTHING AT ONCE. AVOID CONTACT WITH EYES AND SKIN. AVOID BREATHING VAPORS. FOR INDUSTRIAL USE ONLY. WEAR APPROPRIATE SAFETY EQUIPMENT WHEN HANDLING.

STORAGE: DO NOT STORE NEAR INCOMPATIBLES. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE.

=====|
SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION
=====|

ENGINEERING CONTROLS: GENERAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO MINIMIZE VAPOR CONCENTRATIONS. LOCAL EXHAUST MAY BE REQUIRED.

RESPIRATORY PROTECTION: WEAR A PROPERLY FITTED NIOSH/MSHA APPROVED RESPIRATOR WHEN EXPOSURE TO MISTS OR VAPORS IS LIKELY.

SKIN PROTECTION: IMPERVIOUS RUBBER OR NEOPRENE TYPE. CONSULT GLOVE MANUFACTURER FOR RECOMMENDATIONS.

EYE PROTECTION: SAFETY GLASSES WITH SIDE SHIELDS RECOMMENDED AS MINIMUM PROTECTION. GOGGLES RECOMMENDED FOR INDIVIDUALS MIXING THE RESIN AND CATALYST.

OTHER PROTECTIVE EQUIPMENT: CLEAN, FULL BODY COVERING TO MINIMIZE SKIN CONTACT WITH MATERIAL. AN EYEWASH STATION AND SAFETY SHOWER IS RECOMMENDED NEAR WORK AREA.

HYGIENIC PRACTICES: SMOKING OR EATING IN THE WORK AREA SHOULD NOT BE PERMITTED. WASH THOROUGHLY AFTER HANDLING MATERIAL.

=====|
SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES
=====|

BOILING RANGE : 401 - 500 F VAPOR DENSITY : Is heavier than air
ODOR : CHARACTERISTIC ODOR THRESHOLD : NE
APPEARANCE : VISCOUS LIQUID EVAPORATION RATE: Is slower than Ether
SOLUBILITY IN H2O : PARTIAL

(Continued on Page 4)

=====

===== |
| SECTION 15 - REGULATORY INFORMATION |
|=====

THE FOLLOWING COMPONENTS ARE NOT SUBJECT TO REPORTING IN SECTION 2:

----- CHEMICAL NAME ----- CAS NUMBER WT/WT % IS LESS THAN
No non-hazardous components exist

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD CHRONIC HEALTH HAZARD

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME ----- CAS NUMBER WT/WT % IS LESS THAN
No SARA Section 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

The chemical substances in this product are on the TSCA Section 8 Inventory.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

----- CHEMICAL NAME ----- CAS NUMBER
No information is available.

U.S. STATE REGULATIONS: AS FOLLOWS -

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product:

----- CHEMICAL NAME ----- CAS NUMBER
No non-hazardous materials are among the top five ingredients.

PENNSYLVANIA RIGHT-TO-KNOW:

The following non-hazardous ingredients are present in the product at greater than 3%:

----- CHEMICAL NAME ----- CAS NUMBER
No non-hazardous ingredients are present at greater than 3%.

(Continued on Page 6)

=====

