

-----  
M A T E R I A L   S A F E T Y   D A T A   S H E E T  
-----

=====

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

=====

PRODUCT NAME : PRIMER 67C COMPONENT A  
IDENTIFICATION NUMBER: PR67CA00000A PREPARE / REVISED: 08/07/06  
PRODUCT USE/CLASS : CONDUCTIVE EPOXY PRIMER

SUPPLIER: MANUFACTURER:  
Dudick, Inc. Dudick, Inc.  
1818 Miller Parkway 1818 Miller Parkway  
Streetsboro, Ohio 44241 Streetsboro, Ohio 44241

CHEM-TEL: 800-255-3924 CHEM-TEL: 800-255-3924  
24 HOURS A DAY 24 HOURS A DAY

PREPARER: DUDICK, INC., PHONE: 800-322-1970

=====

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

=====

| ITEM | CHEMICAL NAME                   | CAS NUMBER  | WT/WT %<br>LESS THAN |
|------|---------------------------------|-------------|----------------------|
| 01   | BISPHENOL A EPOXY RESIN         | 025085-99-8 | 35.0 %               |
| 02   | CARBON                          | 7782-42-5   | 30.0 %               |
| 03   | BISPHENOL A EPOXY RESIN         | 25085-99-8  | 20.0 %               |
| 04   | ALIPHATIC GLYCIDYL ETHER        | 68609-97-2  | 15.0 %               |
| 05   | EPOXY PHENOL NOVALAC RESIN      | 39817-09-9  | 5.0 %                |
| 06   | PIGMENT DISPERSION              | MIXTURE     | 5.0 %                |
| 07   | PROPYLENE GLYCOL GLYCIDYL ETHER | 009072-62-2 | 5.0 %                |

| ITEM | EXPOSURE LIMITS |          |             |             |         |      |
|------|-----------------|----------|-------------|-------------|---------|------|
|      | ACGIH           |          | OSHA        |             | COMPANY |      |
|      | TLV-TWA         | TLV-STEL | PEL-TWA     | PEL-CEILING | TLV-TWA | SKIN |
| 01   | NE              | NE       | NE          | NE          | NE      | YES  |
| 02   | 3mg/m3 DUST     | NO INFO  | 3mg/m3 DUST | NO INFO     | NE      | NO   |
| 03   | NO INFO         | NO INFO  | NO INFO     | NO INFO     | NE      | YES  |
| 04   | NE              | NE       | NO INFO     | NO INFO     | NE      | YES  |
| 05   | NE              | NE       | NE          | NE          | NE      | YES  |
| 06   | NE              | NE       | NE          | NE          | NE      | NO   |
| 07   | NE              | NE       | NE          | NE          | NE      | YES  |

(See Section 16 for abbreviation legend)

=====

SECTION 3 - HAZARDS IDENTIFICATION

=====

\*\*\* EMERGENCY OVERVIEW \*\*\*: CAUTION!...MAY CAUSE EYE AND SKIN IRRITATION.

(Continued on Page 2)

=====

```

=====
|                                     |
|                               SECTION 3 - HAZARDS IDENTIFICATION                               |
|                                     |
=====

```

EFFECTS OF OVEREXPOSURE - EYE CONTACT: MODERATE EYE IRRITANT.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: MODERATE SKIN IRRITANT. MAY CAUSE REDNESS AND SWELLING IN INDIVIDUALS ALLERGIC TO EPOXY RESINS.

EFFECTS OF OVEREXPOSURE - INHALATION: LOW VOLITILITY. PRODUCT IS NOT EXPECTED TO BE A MAJOR INHALATION HAZARD.

EFFECTS OF OVEREXPOSURE - INGESTION: THIS PRODUCT HAS A LOW ORDER ORAL TOXICITY.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: ALLERGIC REACTIONS MAY OCCUR IN SOME INDIVIDUALS. PREEXISTING SKIN AND EYE DISORDERS MAY BE AGGRAVATED BY THIS PRODUCT. PREEXISTING SKIN OR LUNG INJURIES MAY INCREASE THE CHANCE OF DEVELOPING ALLERGY SYMPTOMS FROM EXPOSURE TO THIS PRODUCT. MAY CAUSE SKIN SENSITIZATION.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT SKIN ABSORPTION INHALATION INGESTION EYE CONTACT

```

=====
|                                     |
|                               SECTION 4 - FIRST AID MEASURES                               |
|                                     |
=====

```

FIRST AID - EYE CONTACT: HOLD OPEN EYE LIDS AND FLUSH WITH COPIOUS AMOUNTS OF FLOWING WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION.

FIRST AID - SKIN CONTACT: WASH AFFECTED AREAS THOROUGHLY WITH SOAP AND WATER. IF SYMPTOMS PERSIST,SEEK MEDICAL ATTENTION. REMOVE CONTAMINATED CLOTHING AND WASH THOROUGHLY BEFORE REUSE.

FIRST AID - INHALATION: REMOVE VICTIM TO FRESH AIR. IF VICTIM IS NOT BREATHING, ARTIFICIAL RESPIRATION SHOULD BE ADMINISTERED BY QUALIFIED PERSONNEL.

FIRST AID - INGESTION: DO NOT INDUCE VOMITING.SEEK MEDICAL ATTENTION. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. GIVE VICTIM PLENTY OF WATER TO DRINK IF CONSCIOUS.

```

=====
|                                     |
|                               SECTION 5 - FIRE FIGHTING MEASURES                               |
|                                     |
=====

```

FLASH POINT: 201 F  
(SETAFLASH CLOSED CUP)

LOWER EXPLOSIVE LIMIT: N.A.  
UPPER EXPLOSIVE LIMIT: N.A.

AUTOIGNITION TEMPERATURE: NE

EXTINGUISHING MEDIA: ALCOHOL FOAM CO2 DRY CHEMICAL FOAM WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: TOXIC FUMES MAY BE PRODUCED IF THIS PRODUCT IS INVOLVED IN A FIRE.

SPECIAL FIREFIGHTING PROCEDURES: EVACUATE AREA. FIGHT FIRE FROM A SAFE

(Continued on Page 3)

=====



=====|  
SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES  
=====|

BOILING RANGE : 500 - 500 F VAPOR DENSITY : Is heavier than air  
ODOR : SLIGHT SOLVENT ODOR THRESHOLD : NE  
APPEARANCE : BLACK LIQUID EVAPORATION RATE: Is slower than Ether  
SOLUBILITY IN H2O : NEGLIGIBLE  
FREEZE POINT : NE SPECIFIC GRAVITY: 1.0831  
VAPOR PRESSURE : NE pH @ 0.0 % : NA  
PHYSICAL STATE : LIQUID VISCOSITY : NA  
COEFFICIENT OF WATER/OIL DISTRIBUTION: NA

(See Section 16 for abbreviation legend)

=====|  
SECTION 10 - STABILITY AND REACTIVITY  
=====|

CONDITIONS TO AVOID: HEAT, FLAME, CONTAMINANTS. DO NOT MIX WITH HARDENER COMPONENT AND LEAVE UNATTENDED. CONSIDERABLE HEAT AND SMOKE MAY EVOLVE CREATING HAZARDOUS CONDITIONS.

INCOMPATIBILITY: STRONG OXIDANTS. STRONG ACIDS. STRONG ALKALIS.

HAZARDOUS DECOMPOSITION PRODUCTS: BURNING WILL PRODUCE TOXIC FUMES. OXIDES OF CARBON. OTHER TOXIC ORGANIC SUBSTANCES MAY BE FORMED.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

=====|  
SECTION 11 - TOXICOLOGICAL PROPERTIES  
=====|

No product or component toxicological information is available.

=====|  
SECTION 12 - ECOLOGICAL INFORMATION  
=====|

ECOLOGICAL INFORMATION: DO NOT CONTAMINATE PONDS, STREAMS, OR UNDERGROUND WATER SUPPLY. PREVENT FROM ENTERING SEWERS.

=====|  
SECTION 13 - DISPOSAL CONSIDERATIONS  
=====|

DISPOSAL METHOD: FOLLOW ALL RELEVANT LOCAL, STATE, AND FEDERAL REGULATIONS. AS MANUFACTURED, IF THIS PRODUCT IS DISCARDED, IT WOULD NOT BE A HAZARDOUS WASTE AS DEFINED BY RCRA. EMPTY DRUMS MAY CONTAIN RESIDUE OR FUMES WHICH ARE HARMFUL. DO NOT WELD,GRIND,OR USE CUTTING TORCHES ON EMPTY DRUMS.

(Continued on Page 5)

=====

=====|  
| SECTION 14 - TRANSPORTATION INFORMATION |  
|=====|

DOT PROPER SHIPPING NAME: PLASTIC LIQUID MATERIAL

DOT TECHNICAL NAME: NA

DOT HAZARD CLASS: NON-REGULATED      HAZARD SUBCLASS: NA

DOT UN/NA NUMBER: NA      PACKING GROUP: NA      RESP. GUIDE PAGE:

=====|  
| SECTION 15 - REGULATORY INFORMATION |  
|=====|

THE FOLLOWING COMPONENTS ARE NOT SUBJECT TO REPORTING IN SECTION 2:

| ----- CHEMICAL NAME -----       | CAS NUMBER | WT/WT % IS LESS THAN |
|---------------------------------|------------|----------------------|
| WETTING AGENT                   | NO INFO    | 1.0 %                |
| ACRYLIC COPOLYMER               | 26376-86-3 | 0.1 %                |
| XYLENE, MIXED ISOMERS           | 1330-20-7  | 0.1 %                |
| ETHYLBENZENE                    | 100-41-4   | 0.1 %                |
| METHOXY PROPANOL ACETATE        | 108-65-6   | 0.1 %                |
| ANTIFOAM POLYMERS/POLYSILOXANES | MIXTURE    | 0.1 %                |
| N-BUTYL ACETATE                 | 123-86-4   | 0.1 %                |

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD    CHRONIC HEALTH HAZARD

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

| ----- CHEMICAL NAME ----- | CAS NUMBER | WT/WT % IS LESS THAN |
|---------------------------|------------|----------------------|
| XYLENE, MIXED ISOMERS     | 1330-20-7  | 0.1 %                |
| ETHYLBENZENE              | 100-41-4   | 0.1 %                |

TOXIC SUBSTANCES CONTROL ACT:

The chemical substances in this product are not on the TSCA Section 8 Inventory.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

----- CHEMICAL NAME -----      CAS NUMBER  
No information is available.

(Continued on Page 6)

=====

