


(Continued on Page 2)



=====|
| SECTION 3 - HAZARDS IDENTIFICATION |
=====|

EFFECTS OF OVEREXPOSURE - INHALATION: MAY CAUSE SLURRED SPEECH, DIZZINESS, GIDDINESS, AND POSSIBLE LOSS OF CONSCIOUSNESS. CONCENTRATIONS OF 10,000 PPM OF XYLENE CAN BE IMMEDIATELY DANGEROUS TO LIFE AND HEALTH.

EFFECTS OF OVEREXPOSURE - INGESTION: INGESTION MAY CAUSE NAUSEA, CRAMPS, VOMITING, AND DIARRHEA. ASPIRATION HAZARD. PRODUCT MAY ENTER THE LUNGS DURING SWALLOWING AND CAUSE LUNG DAMAGE.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: PREEXISTING SKIN OR LUNG INJURIES MAY INCREASE THE CHANCE OF DEVELOPING ALLERGY SYMPTOMS FROM EXPOSURE TO THIS PRODUCT. CHRONIC LONG TERM OVEREXPOSURE OR INTENTIONAL ABUSE, MISUSE, OR OTHER MASSIVE EXPOSURE TO SOLVENT CONTAINING PRODUCTS MAY CAUSE MULTIPLE ORGAN DAMAGE AND/OR DEATH. CHRONIC INHALATION AT HIGH EXPOSURES (3000PPM) CAUSED A SLIGHT INCREASE IN LIVER WEIGHT IN FEMALE RATS AND MICE AND SLIGHT EFFECT ON KIDNEY FUNCTIONS. THE TALC CONTAINED IN THIS PRODUCT IS NOT IN ITS FREE STATE AND SHOULD BE A HEALTH CONCERN ONLY IF GRINDING OR SANDING THE CURED MATERIAL.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT INHALATION INGESTION EYE CONTACT

=====|
| SECTION 4 - FIRST AID MEASURES |
=====|

FIRST AID - EYE CONTACT: HOLD OPEN EYE LIDS AND FLUSH WITH COPIOUS AMOUNTS OF FLOWING WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION.

FIRST AID - SKIN CONTACT: WASH AFFECTED AREAS THOROUGHLY WITH SOAP AND WATER. IF SYMPTOMS PERSIST, SEEK MEDICAL ATTENTION. REMOVE CONTAMINATED CLOTHING AND WASH THOROUGHLY BEFORE REUSE.

FIRST AID - INHALATION: REMOVE VICTIM TO FRESH AIR. IF VICTIM IS NOT BREATHING, ARTIFICIAL RESPIRATION SHOULD BE ADMINISTERED BY QUALIFIED PERSONNEL.

FIRST AID - INGESTION: IF SWALLOWED, CALL A PHYSICIAN IMMEDIATELY. REMOVE CONTENTS OF STOMACH ONLY AS DIRECTED BY MEDICAL PERSONNEL.

=====|
| SECTION 5 - FIRE FIGHTING MEASURES |
=====|

FLASH POINT: 102 F
(SETAFLASH CLOSED CUP)

LOWER EXPLOSIVE LIMIT: 1.0 %
UPPER EXPLOSIVE LIMIT: 13.1 %

AUTOIGNITION TEMPERATURE: NE

EXTINGUISHING MEDIA: ALCOHOL FOAM CO2 DRY CHEMICAL FOAM WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL A LONG DISTANCE AND FLASH BACK.

SPECIAL FIREFIGHTING PROCEDURES: EVACUATE AREA. WATER MAY BE INEFFECTIVE

(Continued on Page 3)

=====

SECTION 5 - FIRE FIGHTING MEASURES

BUT MAY BE USED TO COOL FIRE EXPOSED CONTAINERS. FIGHT FIRE FROM A SAFE DISTANCE. WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: ABSORB EXCESS WITH SAND, EARTH, OR VERMICULITE. SCRAPE UP AND PLACE IN SUITABLE CONTAINER FOR DISPOSAL. WEAR ALL APPROPRIATE SAFETY EQUIPMENT WHILE HANDLING SPILLS. USE NON-SPARKING TOOLS.

SECTION 7 - HANDLING AND STORAGE

HANDLING: AVOID CONTACT WITH EYES AND SKIN. AVOID BREATHING VAPORS. FOR INDUSTRIAL USE ONLY. WEAR APPROPRIATE SAFETY EQUIPMENT WHEN HANDLING.

STORAGE: DO NOT STORE NEAR INCOMPATIBLES. DO NOT STORE NEAR EXCESSIVE HEAT OR NEAR SOURCES OF IGNITION. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. THIS MATERIAL IS HYGROSCOPIC. AVOID CONTAMINATION WITH MOISTURE.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: GENERAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO MINIMIZE VAPOR CONCENTRATIONS. LOCAL EXHAUST MAY BE REQUIRED.

RESPIRATORY PROTECTION: WEAR A PROPERLY FITTED NIOSH APPROVED RESPIRATOR WHEN THE TLV IS EXCEEDED.

SKIN PROTECTION: IMPERVIOUS RUBBER OR NEOPRENE TYPE. CONSULT GLOVE MANUFACTURER FOR RECOMMENDATIONS.

EYE PROTECTION: USE SPLASH-PROOF GOGGLES OR FACE SHIELD WHEN EYE CONTACT MAY OCCUR. SAFETY GLASSES WITH SIDE SHIELDS RECOMMENDED AS MINIMUM PROTECTION. GOGGLES RECOMMENDED FOR INDIVIDUALS MIXING THE RESIN AND CATALYST.

OTHER PROTECTIVE EQUIPMENT: CLEAN, FULL BODY COVERING TO MINIMIZE SKIN CONTACT WITH MATERIAL. AN EYEWASH STATION AND SAFETY SHOWER IS RECOMMENDED NEAR WORK AREA.

HYGIENIC PRACTICES: SMOKING OR EATING IN THE WORK AREA SHOULD NOT BE PERMITTED. WASH THOROUGHLY AFTER HANDLING MATERIAL.

(Continued on Page 4)

=====|
| SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES |
=====|

BOILING RANGE : 275 - 320 F VAPOR DENSITY : Is heavier than air
ODOR : SOLVENT ODOR THRESHOLD : NE
APPEARANCE : VISCOUS LIQUID EVAPORATION RATE: Is slower than Ether
SOLUBILITY IN H2O : NEGLIGIBLE
FREEZE POINT : NE SPECIFIC GRAVITY: 1.0885
VAPOR PRESSURE : NE pH @ 0.0 % : NE
PHYSICAL STATE : LIQUID VISCOSITY : NE
COEFFICIENT OF WATER/OIL DISTRIBUTION: NE

(See Section 16 for abbreviation legend)

=====|
| SECTION 10 - STABILITY AND REACTIVITY |
=====|

CONDITIONS TO AVOID: HEAT, FLAME, CONTAMINANTS.

INCOMPATIBILITY: STRONG OXIDANTS. THIS PRODUCT CONTAINS TRIMETHYLOL PROPANE AND SHOULD NOT BE MIXED WITH PHOSPHORUS-CONTAINING MATERIAL BECAUSE HIGHLY TOXIC FUMES CAN BE EMITTED IN A FIRE SITUATION.

HAZARDOUS DECOMPOSITION PRODUCTS: OXIDES OF CARBON.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

=====|
| SECTION 11 - TOXICOLOGICAL PROPERTIES |
=====|

No product or component toxicological information is available.

=====|
| SECTION 12 - ECOLOGICAL INFORMATION |
=====|

ECOLOGICAL INFORMATION: DO NOT CONTAMINATE PONDS, STREAMS, OR UNDERGROUND WATER SUPPLY.

=====|
| SECTION 13 - DISPOSAL CONSIDERATIONS |
=====|


DISPOSAL METHOD: FOLLOW ALL RELEVANT LOCAL, STATE, AND FEDERAL REGULATIONS. DO NOT WELD, GRIND, OR USE CUTTING TORCHES ON EMPTY DRUMS.

=====|
| SECTION 14 - TRANSPORTATION INFORMATION |
=====|

DOT PROPER SHIPPING NAME: RESIN SOLUTION

DOT TECHNICAL NAME: NA

(Continued on Page 5)



=====
 SECTION 14 - TRANSPORTATION INFORMATION
 =====

DOT HAZARD CLASS: 3

HAZARD SUBCLASS: NA

DOT UN/NA NUMBER: UN1866

PACKING GROUP: III

RESP. GUIDE PAGE: 127

 =====
 SECTION 15 - REGULATORY INFORMATION
 =====

THE FOLLOWING COMPONENTS ARE NOT SUBJECT TO REPORTING IN SECTION 2:

----- CHEMICAL NAME -----	CAS NUMBER	WT/WT % IS LESS THAN
SATURATED POLYESTER POLYOL	UNKNOWN	35.0 %
TITANIUM DIOXIDE	13463-67-7	10.0 %
POLYPROPYLENE HOMOPOLYMER	9003-07-0	1.0 %
CELLULOSE ACETATE BUTYRATE	9004-36-8	1.0 %
CLAY	MIXTURE	1.0 %
PIGMENT	MIXTURE	1.0 %
UNSATURATED POLYCARBOXYLIC ACID	MIXTURE	1.0 %
POLYCARBOXYLIC ACID,POLYSILOXANE COPO	MIXTURE	1.0 %
PIGMENT	MIXTURE	1.0 %
ACRYLIC COPOLYMER	26376-86-3	1.0 %
ORGANO-SILICONE	MIXTURE	0.1 %
DIBUTYL TIN DILAURATE	77-58-7	0.1 %
2,6-DIMETHYL-4-HEPTANONE	108-83-8	0.1 %
4,6-DIMETHYL-2-HEPTANONE	19549-80-5	0.1 %

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD CHRONIC HEALTH HAZARD FIRE HAZARD

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME -----	CAS NUMBER	WT/WT % IS LESS THAN
XYLENE,MIXED ISOMERS	1330-20-7	15.0 %
ETHYLBENZENE	100-41-4	5.0 %

TOXIC SUBSTANCES CONTROL ACT:

The chemical substances in this product are on the TSCA Section 8 Inventory.

(Continued on Page 6)

=====|
| SECTION 15 - REGULATORY INFORMATION |
=====|

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

----- CHEMICAL NAME ----- CAS NUMBER
No information is available.

U.S. STATE REGULATIONS: AS FOLLOWS -

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product:

----- CHEMICAL NAME ----- CAS NUMBER
SATURATED POLYESTER POLYOL UNKNOWN
TITANIUM DIOXIDE 13463-67-7

PENNSYLVANIA RIGHT-TO-KNOW:

The following non-hazardous ingredients are present in the product at greater than 3%:

----- CHEMICAL NAME ----- CAS NUMBER
SATURATED POLYESTER POLYOL UNKNOWN
TITANIUM DIOXIDE 13463-67-7

CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

----- CHEMICAL NAME ----- CAS NUMBER
No Proposition 65 chemicals exist in this product.

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: B

=====|
| SECTION 16 - OTHER INFORMATION |
=====|

HMIS RATINGS - HEALTH: 2 FLAMMABILITY: 2 REACTIVITY: 1

VOLATILE ORGANIC COMPOUNDS (VOCS): 4.64 lbs/gal, 556 grams/ltr

LEGEND: N.A. - Not Applicable, N.E. - Not Established,
N.D. - Not Determined

=====
(Continued on Page 7)
=====

DISCLAIMER

The information contained on this MSDS has been compiled from information

obtained from raw material suppliers and is believed to be accurate. It is the responsibility of the user to comply with all Federal, State and Local Regulations.

=====

<END OF MSDS>