

-----  
M A T E R I A L   S A F E T Y   D A T A   S H E E T  
-----

=====

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

=====

PRODUCT NAME : PH-1 HARDENER  
IDENTIFICATION NUMBER: PH-1HARD000B PREPARE / REVISED: 08/07/06  
PRODUCT USE/CLASS : POLYESTER/VINYL ESTER HARDENER

SUPPLIER: Dudick, Inc. 1818 Miller Parkway Streetsboro, Ohio 44241	MANUFACTURER: Dudick, Inc. 1818 Miller Parkway Streetsboro, Ohio 44241
CHEM-TEL: 800-255-3924 24 HOURS A DAY	CHEM-TEL: 800-255-3924 24 HOURS A DAY

PREPARER: DUDICK, INC PHONE: 800-322-1970

=====

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

=====

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % LESS THAN
01	CUMENE HYDROPEROXIDE	80-15-9	85.0 %
02	CUMENE	98-82-8	15.0 %

ITEM	EXPOSURE LIMITS					
	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL-CEILING	COMPANY TLV-TWA	SKIN
01	50PPM	50PPM	NO INFO	NO INFO	NE	YES
02	246 mg/M3	NO INFO	245 mg/M3	NO INFO	NE	YES

(See Section 16 for abbreviation legend)

=====

SECTION 3 - HAZARDS IDENTIFICATION

=====

\*\*\* EMERGENCY OVERVIEW \*\*\*: DANGER!---ORGANIC PEROXIDE. HEAT OR CONTAMINATION MAY CAUSE HAZARDOUS DECOMPOSITION. RESPIRATORY TRACT IRRITANT. WARNING!...SEVERE EYE AND SKIN IRRITANT. KEEP AWAY FROM ALL SOURCES OF IGNITION. STORE OUT OF DIRECT SUNLIGHT IN A COOL, WELL VENTILATED AREA. MAY BE FATAL IF SWALLOWED.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: EYE CONTACT MAY CAUSE SEVERE IRRITATION WITH CORNEAL INJURY. MAY CAUSE BLINDNESS.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: PROLONGED EXPOSURE MAY CAUSE SKIN IRRITATION AND BURNS. SEVERE SKIN IRRITANT.

(Continued on Page 2)

=====



=====  
SECTION 5 - FIRE FIGHTING MEASURES  
=====

BUT MAY BE USED TO COOL FIRE EXPOSED CONTAINERS. FIGHT FIRE FROM A SAFE DISTANCE. WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING.

=====  
SECTION 6 - ACCIDENTAL RELEASE MEASURES  
=====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: DIKE AREA TO CONTAIN SPILLAGE. ABSORB EXCESS WITH SAND, EARTH, OR VERMICULITE. SCRAPE UP AND PLACE IN SUITABLE CONTAINER FOR DISPOSAL. WEAR ALL APPROPRIATE SAFETY EQUIPMENT WHILE HANDLING SPILLS. USE NON-SPARKING TOOLS. IF A SPILL OR LEAK OCCURS IN EXCESS OF THE RQ, NOTIFY THE NATIONAL RESPONSE CENTER (1-800-424-8802).

=====  
SECTION 7 - HANDLING AND STORAGE  
=====

HANDLING: IF BODILY CONTACT OCCURS, REMOVE CONTAMINATED CLOTHING AT ONCE. AVOID CONTACT WITH EYES AND SKIN. AVOID BREATHING VAPORS. FOR INDUSTRIAL USE ONLY. WEAR APPROPRIATE SAFETY EQUIPMENT WHEN HANDLING.

STORAGE: DO NOT STORE NEAR INCOMPATIBLES. DO NOT STORE NEAR EXCESSIVE HEAT OR NEAR SOURCES OF IGNITION. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. BUNGS MUST BE KEPT TIGHTLY CLOSED WHEN CONTAINERS ARE NOT IN USE OR ARE PLACED IN STORAGE AREAS.

=====  
SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION  
=====

ENGINEERING CONTROLS: GENERAL MECHANICAL VENTILATION MAY BE SUFFICIENT TO MINIMIZE VAPOR CONCENTRATIONS. LOCAL EXHAUST MAY BE REQUIRED.

RESPIRATORY PROTECTION: WEAR A PROPERLY FITTED NIOSH/MSHA APPROVED RESPIRATOR WHEN EXPOSURE TO MISTS OR VAPORS IS LIKELY.

SKIN PROTECTION: IMPERVIOUS RUBBER OR NEOPRENE TYPE. CONSULT GLOVE MANUFACTURER FOR RECOMMENDATIONS.

EYE PROTECTION: SAFETY GLASSES WITH SIDE SHIELDS RECOMMENDED AS MINIMUM PROTECTION. GOGGLES RECOMMENDED FOR INDIVIDUALS MIXING THE RESIN AND CATALYST.

OTHER PROTECTIVE EQUIPMENT: CLEAN, FULL BODY COVERING TO MINIMIZE SKIN CONTACT WITH MATERIAL. AN EYEWASH STATION AND SAFETY SHOWER IS RECOMMENDED NEAR WORK AREA.

HYGIENIC PRACTICES: SMOKING OR EATING IN THE WORK AREA SHOULD NOT BE PERMITTED. WASH THOROUGHLY AFTER HANDLING MATERIAL.

(Continued on Page 4)

=====

=====  
SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES  
=====

BOILING RANGE : N.A.                      VAPOR DENSITY : Is heavier than air  
ODOR : SHARP,AROMATIC      ODOR THRESHOLD : NE  
APPEARANCE : LIQUID-CLEAR-YEL.EVAPORATION RATE: Is slower than Ether  
SOLUBILITY IN H2O : SLIGHT  
FREEZE POINT : NE                      SPECIFIC GRAVITY: 1.05  
VAPOR PRESSURE : 13.9mmHG @68 F      pH @ 0.0 % : NE  
PHYSICAL STATE : LIQUID              VISCOSITY : NE  
COEFFICIENT OF WATER/OIL DISTRIBUTION: NE

(See Section 16 for abbreviation legend)

=====  
SECTION 10 - STABILITY AND REACTIVITY  
=====

CONDITIONS TO AVOID: HEAT, FLAME, CONTAMINANTS. UNDER NO CIRCUMSTANCES SHOULD THIS MATERIAL BE HEATED. A VIOLENT EXOTHERMIC REACTION CAN OCCUR. NEVER USE DRUM WARMERS ON THIS MATERIAL.

INCOMPATIBILITY: STRONG OXIDANTS. STRONG ACIDS. AMINES. SULFURIC ACID. STRONG ALKALIS. REDUCING AGENTS. TRANSITION METALS.

HAZARDOUS DECOMPOSITION PRODUCTS: BURNING WILL PRODUCE TOXIC FUMES. OXIDES OF CARBON.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

=====  
SECTION 11 - TOXICOLOGICAL PROPERTIES  
=====

No product or component toxicological information is available.

=====  
SECTION 12 - ECOLOGICAL INFORMATION  
=====

ECOLOGICAL INFORMATION: THE ECOLOGICAL TOXICITY OF THIS PRODUCT IS NOT KNOWN.

=====  
SECTION 13 - DISPOSAL CONSIDERATIONS  
=====

DISPOSAL METHOD: FOLLOW ALL RELEVANT LOCAL, STATE, AND FEDERAL REGULATIONS. THIS PRODUCT AND ANY ABSORBENTS USED IN SPILL CLEANUP ARE HAZARDOUS WASTES AND MUST BE DISPOSED OF ACCORDINGLY. DO NOT WELD,GRIND,OR USE CUTTING TORCHES ON EMPTY DRUMS. THIS PRODUCT EXHIBITS THE CHARACTERISTIC OF REACTIVITY PER RCRA AND MUST BE DISPOSED OF ACCORDINGLY. EMPTY CONTAINERS CONTAIN PRODUCT RESIDUE WHICH IS HAZARDOUS.DO NOT WELD,BRAZE, OR GRIND.KEEP AWAY FROM HEAT,FLAME, AND SOURCES OF IGNITION.DO NOT REUSE EMPTY CONTAINERS.

(Continued on Page 5)

=====



```

=====
|                                     |
|                               SECTION 15 - REGULATORY INFORMATION                               |
|                                     |
=====

```

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product:

----- CHEMICAL NAME -----	CAS NUMBER
PHthalate Plasticizer	UNKNOWN

PENNSYLVANIA RIGHT-TO-KNOW:

The following non-hazardous ingredients are present in the product at greater than 3%:

----- CHEMICAL NAME -----	CAS NUMBER
PHthalate Plasticizer	UNKNOWN

CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

----- CHEMICAL NAME -----	CAS NUMBER
No Proposition 65 chemicals exist in this product.	

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: F

```

=====
|                                     |
|                               SECTION 16 - OTHER INFORMATION                               |
|                                     |
=====

```

HMIS RATINGS - HEALTH: 3      FLAMMABILITY: 2      REACTIVITY: 4

VOLATILE ORGANIC COMPOUNDS (VOCs): 0.00 lbs/gal,    0 grams/ltr

LEGEND: N.A. - Not Applicable, N.E. - Not Established,  
N.D. - Not Determined

=====

The information contained on this MSDS has been compiled from information obtained from raw material suppliers and is believed to be accurate. It is the responsibility of the user to comply with all Federal, State and Local Regulations.

=====  
<END OF MSDS>