

DATE PRINTED 7/17/2017 SDS REF. No: #PR200WBA

SAFETY DATA SHEET

PRIMER 200 WATER BASED URETHANE COMP. A

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: PRIMER 200 WATER BASED URETHANE COMP. A

PRODUCT CODE: #PR200WBA

PRODUCT USE: Polyol component of water borne 2 part Urethane top coat.

MANUFACTURER24 HR. EMERGENCY TELEPHONE NUMBERDUDICK, INC.CHEM-TEL (US Transportation): (800)255-39241818 MILLER PARKWAYCHEM-TEL (International : +01-813-248-0585

STREETSBORO, OH, 44241 Transportation)

330-562-1970

2. HAZARDS IDENTIFICATION

CLASSIFICATION:

No Hazard classification applies

GHS LABEL ELEMENTS:

None Apply

SIGNAL WORD: None applies

HAZARD STATEMENTS:

No hazard statements apply.

PRECAUTIONARY STATEMENTS:

General Precaution:

Observe good industrial hygiene practices.

3. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

This product contains an amine neutralizing agent which is bound in the matrix of this product as a salt. This amine salt is considered essentially unreactive at room temperature. Generation of amine vapors is expected when this product is processed (heated) during the drying/hardening of the coating.

4. FIRST AID MEASURES

EYES: Hold open eyelids and flush with copious amounts of water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, get medical advice/attention.

SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

INGESTION: Rinse mouth out with water.

Do not induce vomiting without medical advice.

Consult physician.

INHALATION: If inhaled, remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

DATE PRINTED	7/17/2017
SDS REF. No:	#PR200WBA

NOTES TO PHYSICIAN: No data available for this product.

5. FIRE FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Alcohol resistant foam; Carbon Dioxide (CO2); dry chemical; dry sand; use water to keep containers cool.

UNSUITABLE EXTINGUISHING MEDIA: Do not use high pressure water jet as this may spread the area of the fire.

SPECIFIC HAZARDS IN CASE OF FIRE: Closed containers may rupture (due to build up in pressure) when exposed to extreme heat.

Burning may produce noxious and toxic fumes. Incomplete combustion may form carbon monoxide.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTION FOR FIRE FIGHTERS: Wear self-contained breathing apparatus (SCBA) in positive pressure mode and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Isolate area. Keep unnecessary and unprotected personnel from entering the area. Use appropriate safety equipment.

ENVIRONMENTAL PRECAUTIONS: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater.

METHOD AND MATERIALS FOR CONTAINMENT AND CLEANING UP: Cover spill with inert material (e. g., dry sand or earth) and collect for proper disposal. Wash spill area with soap and water. Ventilate area to remove vapors or dust.

7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING: Avoid prolonged or repeated contact with skin. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.

CONDITIONS FOR SAFE STORAGE, INCLUDING INCOMPATIBILITIES: Protect from

freezing. Store in a cool dry place. Store in original or similar containers.

Storage Temperature Minimum: 5° C (41° F) Maximum: 35° C (95° F)

8. EXPOSURE CONTROLS\PERSONAL PROTECTION

EXPOSURE LIMITS

None established

ENGINEERING CONTROLS: Ventilation:

Use local exhaust ventilation, or other engineering controls to maintain airborne levels requirements or guidelines, general ventilation should be sufficient for most operations.

PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION: For most conditions, no respiratory protection should be needed; however, if material is heated or sprayed, use a NIOSH/MHSA approved respirator with organic vapor cartridge. For spray applications or other situations such as high temperature use which may produce inhalation exposures, a supplied-air respirator (either positive pressure or continuous flow-type) is recommended.

EYES PROTECTION: Use safety glasses (with side shields) as minimum protection. Goggles recommended for individuals mixing the resin and catalyst.

SKIN PROTECTION: Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Hand protection: Use chemical resistant gloves. Consult glove manufacturer for recommendations.

DATE PRINTED	7/17/2017
SDS REF. No:	#PR200WBA

WORK HYGIENIC PRACTICES: Use good personal hygiene. Do not consume or store food in the work area. Wash hands before smoking or eating. Wash contaminated clothing before reuse. **OTHER USE PRECAUTIONS:** The type and degree of personal protective equipment will depend on the specific work operation. Eye wash stations and emergency showers should be available. Inspect and replace personal protective equipment at regular intervals; use professional care in their selection, use and care.

COMMENTS: None.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

COLOR: Varies

FLASH POINT AND METHOD: Not applicable.

AUTO-IGNITION TEMPERATURE: Not Determined.

BOILING POINT/RANGE: No data available for this product.

MELTING POINT: Not Determined.
VAPOUR PRESSURE: Not determined.
VAPOUR DENSITY: Heavier than air.

SOLUBILITY: Miscible in water.

ODOR/THRESHOLD: Mild, characteristic.

LOWER / UPPER FLAMMABLE LIMITS: Not applicable.

DENSITY: 1.0685

EVAPORATION RATE: Slower than ether. **PARTITION COEFFICIENT:** Not determined.

pH: ~ 7.5

DECOMPOSITION TEMPERATURE: Not determined.

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY: This product is stable under normal storage conditions.

POSSIBILITY OF HAZARDOUS REACTIONS: Will not occur under normal conditions.

CONDITIONS TO AVOID: Protect from freezing.

MATERIALS TO AVOID: Water reactives, Acids, strong alkalis, Isocyanates.

HAZARDOUS DECOMPOSITION PRODUCTS: By Fire and Thermal Decomposition: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke, Isocyanate, Isocyanic Acid and other undetermined compounds., Hydrogen cyanide

11. TOXICOLOGICAL INFORMATION

SIGNS AND SYMPTOMS OF OVEREXPOSURE:

ACUTE EFFECTS:

EYE CONTACT: Not expected to cause adverse acute health effects. **SKIN CONTACT:** Not expected to cause adverse acute health effects. **INHALATION:** Not expected to cause adverse acute health effects. **INGESTION:** Not expected to cause adverse acute health effects. **TARGET ORGAN:** Not expected to cause adverse acute health effects.

CHRONIC EFFECTS: Chronic: Not expected to cause adverse chronic health effects.

TOXICITY VALUES: Not determined

12. ECOLOGICAL INFORMATION

PERSISTENCE AND DEGRADABILITY:

Not determined.

BIO-ACCUMULATIVE POTENTIAL:

Not determined.

MOBILITY IN SOIL:

DATE PRINTED	7/17/2017
SDS REF. No:	#PR200WBA

Not determined.

OTHER ADVERSE EFFECTS:

Not known.

ECOTOXICOLOGICAL OTHER INFORMATION:

Not determined.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of according to local, state, and federal regulations through a licensed disposal facility.

14. TRANSPORT INFORMATION

UN NUMBER: Not regulated.

UN PROPER SHIPPING NAME: Not regulated.

TRANSPORT HAZARD CLASS:

Not applicable.

TRANSPORT HAZARD SUBCLASS:

Not applicable.

PACKING GROUP: N/A
MARINE POLLUTANT Y/N:

No

SPECIAL PRE-CAUTIONS: None

15. REGULATORY INFORMATION

U.S. REGULATIONS:

All components of this product are listed on or exempt from the TSCA Inventory.

U.S. SARA TITLE III (SUPERFUND AMENDMENRS AND REAUTHORIZATION ACT) 311/312 HAZARD CATEGORIES:

FIRE: No.

PRESSURE GENERATING: No

REACTIVITY: No ACUTE: No CHRONIC: No

313 REPORTABLE INGREDIENTS:

313 REPORTABLE INGREDIENTS

302/304 EMERGENCY PLANNING

EMERGENCY PLAN: No data available for this product.

STATE REGULATIONS:

The following chemicals are California Proposition 65 reportable:

None known

OTHER GOVT. REGULATIONS: No other information available

DATE PRINTED	7/17/2017
SDS REF. No:	#PR200WBA

16. OTHER INFORMATION

MANUFACTURER DISCLAIMER: The information contained herein is accurate to the best of our knowledge. Dudick, Inc. makes no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances and with respect to the completeness or continuing accuracy of the information contained herein and disclaims all liability for reliance thereon. The information contained on this MSDS has been compiled from information obtained from raw material suppliers and is believed to be accurate. It is the responsibility of the user to ensure that he/she has all of the current data and MSDS relevant to the material thereon and to comply with all Federal, State and Local Regulations.