

Safety Data Sheet

Prepared in Accordance with HCS 29 C.F.R. 1910.1200

1. Identification of the Substance/Mixture and the Company/Undertaking

1.1	Product Identifier	209DA1NL	Revision Date: 1	12/14/2022
	Product Name:	PRIMER 67 DTO Supercedes Date: PART A	New SDS	
1.2	Relevant identified uses of the substance or mixture and uses advised against	Component of multicomponent industrial coatings - Industrial use.		
1.3	Details of the supplier of the safety			
	Manufacturer :			
		Regulatory / Technical Information: 330-562-1970		
	Datasheet Produced by:	n		
1.4	Emergency telephone number:	CHEM-TEL (US Transportation): (800) 2 CHEM-TEL (International Transportation HEALTH: Pittsburgh Poison Control 1-47): +01-813-248-0585	

2. Hazard Identification

2.1 Classification of the substance or mixture

Hazardous to the aquatic environment, Chronic, category 2 Eye Irritation, category 2 Skin Irritation, category 2 Skin Sensitizer, category 1

2.2 Label elements

Symbol(s) of Product



Signal Word

Warning

Named Chemicals on Label

NEOPENTYL GLYCOL DIGLYCIDYL ETHER, BISPHENOL A EPOXY RESIN

HAZARD STATEMENTS

Skin Irritation, category 2 Skin Sensitizer, category 1 Eye Irritation, category 2 Hazardous to the aquatic environment, Chronic, category 2 PRECAUTION PHRASES	H315 H317 H319 H411	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.
	P261 P273 P280 P302+352	Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/ face protection. IF ON SKIN: Wash with plenty of soap and water.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

P305+351+338

P333+313 P391

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous ingredients

Name According to EEC BISPHENOL A EPOXY RESIN	<u>EINEC No.</u> 500-033-5	<u>CAS-No.</u> 25068-38-6	<u>%</u> 75 - 100	Classifications H315-317-319-411	Aquatic Chronic 2, Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1
NEOPENTYL GLYCOL DIGLYCIDYL ETHER	701-333-0	17557-23-2	2.5 - <10	H315-317	Skin Irrit. 2, Skin Sens. 1
TITANIUM DIOXIDE	236-675-5	13463-67-7	0.1 - <1.0		

Continue rinsing.

Collect spillage.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so.

If skin irritation or rash occurs: Get medical advice/attention.

CAS-No.	M-Factors
25068-38-6	0
17557-23-2	0
13463-67-7	0

Remarks: CAS No. 25068-38-6 identified as CAS No. 1675-54-3, EC No. 216-823-5 under REACH Registration CAS No 13463-67-7: Note 10

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

AFTER INHALATION: Give oxygen or artificial respiration if needed. Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. AFTER INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call

AFTER INGESTION: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Harmful if swallowed. May cause sensitization by skin contact. Irritating to eyes and skin. Risk of serious damage to the lungs (by aspiration). Vapours may cause drowsiness and dizziness. Toxic to aquatic organisms.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS: Flammable liquid. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Provide adequate ventilation. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Electrical installations / working materials must comply with the technological safety standards. Wear shoes with conductive soles.

FOR SAFETY REASONS NOT TO BE USED: No Information

5.2 Special hazards arising from the substance or mixture No Information

5.3 Advice for firefighters

SPECIAL FIREFIGHTING PROCEDURES: In the event of fire, wear self-contained breathing apparatus. Cool containers / tanks with water spray. Flammable.

SPECIAL FIREFIGHTING PROTECTION EQUIPMENT: No Information

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Evacuate personnel to safe areas. Remove all sources of ignition. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. For personal protection see section 8.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

No Information

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Prepare the working solution as given on the label(s) and/or the user instructions. Do not breathe vapours or spray mist. Ensure all equipment is electrically grounded before beginning transfer operations. Do not use sparking tools. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection. Wash thoroughly after handling.

PROTECTION AND HYGIENE MEASURES : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Heat, flames and sparks. **STORAGE CONDITIONS:** Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits

(US)

Name	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
BISPHENOL A EPOXY RESIN	25068-38-6	N/E	N/E	N/E
NEOPENTYL GLYCOL DIGLYCIDYL ETH	ER 17557-23-2	N/E	N/E	N/E
TITANIUM DIOXIDE	13463-67-7	10 mg/m3	N/E	N/E
Name	CAS-No.	<u>OSHA PEI</u>	OSHA ST	EL
BISPHENOL A EPOXY RESIN	25068-38-6	N/E	N/E	
NEOPENTYL GLYCOL DIGLYCIDYL ETH	IER 17557-23-2	N/E	N/E	
TITANIUM DIOXIDE	13463-67-7	15 MGM3	N/E	

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required.

EYE PROTECTION: Safety glasses with side-shields.

HAND PROTECTION: Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Request information on glove permeation properties from the glove supplier. Lightweight protective clothing

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location.

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. F	9. Physical and Chemical Properties					
9.1	Information on basic physical and chemical properties Appearance:	viscous Liquid, Various Colors				
	Physical State	Liquid				
	Odor	Ероху				
	Odor threshold	Not Determined				
	рН	Not Determined				
	Melting point / freezing point (°C)	Not Determined				
	Boiling point/range (°C)	500 F (260 C) - 500 F (260 C)				
	Flash Point (°C)	Unknown				
	Evaporation rate	Slower Than Ether				
	Flammability (solid, gas)	N/D				
	Upper/lower flammability or explosive limits	N/A - N/A				
	Vapour Pressure, mmHg	Not Determined				
	Vapour density	Heavier than Air				
	Relative density	N/D				
	Solubility in / Miscibility with water	Not Determined				
	Partition coefficient: n-octanol/water	N/D				
	Auto-ignition temperature (°C)	N/D				
	Decomposition temperature (°C)	N/D				
	Viscosity	Unknown				
	Explosive properties	N/D				
	Oxidising properties	N/D				
9.2	Other information					
	VOC Content g/l:	10				
	Specific Gravity (g/cm3)	1.16				

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11.	11. Toxicological Information						
11.1	1 Information on toxicological effects						
	Acute Toxicity:						
	Oral LD50:	N/D					
	Inhalation LC50: N/D						
	Irritation: Eye Irritation, category 2; Skin Irritation, category 2						
	Corrosivity: Unknown						
	Sensitization:	Skin Sensitizer, category 1					
Repeated dose toxicity: Unknown		Unknown					
	Carcinogenicity:	Unknown					
	Mutagenicity:	Unknown					
Toxicity for reproduction:UnknownSTOT-single exposure:Unknown		Unknown					
		Unknown					
	Unknown						
Aspiration hazard: Unknown							

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	<u>Dust/Mist</u> LC50
BISPHENOL A EPOXY RESIN	11400 mg/kg, rat, oral	23000 mg/kg, dermal, rabbit	>20 mL/kg skin, sensitizer		
NEOPENTYL GLYCOL DIGLYCIDYL ETHER	4500 mg/kg, oral rat	>2000 mg/kg, dermal, rat	Not Available	0.000	0.000
TITANIUM DIOXIDE	25000 mg/kg, oral (rat)	Not Available	Not Available	No Information	No Information
	BISPHENOL A EPOXY RESIN NEOPENTYL GLYCOL DIGLYCIDYL ETHER	BISPHENOL A EPOXY RESIN11400 mg/kg, rat, oralNEOPENTYL GLYCOL DIGLYCIDYL ETHER4500 mg/kg, oral ratTITANIU IM DIOXIDE25000 mg/kg,	BISPHENOL A EPOXY RESIN11400 mg/kg, rat, oral23000 mg/kg, dermal, rabbitNEOPENTYL GLYCOL DIGLYCIDYL ETHER4500 mg/kg, oral rat>2000 mg/kg, dermal, ratTITANII IM DIOXIDE25000 mg/kg, Not Available	BISPHENOL A EPOXY RESIN 11400 mg/kg, rat, oral 23000 mg/kg, dermal, rabbit >20 mL/kg skin, sensitizer NEOPENTYL GLYCOL DIGLYCIDYL ETHER 4500 mg/kg, oral rat >2000 mg/kg, dermal, rat Not Available TITANII IM DIOXIDE 25000 mg/kg, Not Available Not Available Not Available	BISPHENOL A EPOXY RESIN 11400 mg/kg, rat, oral 23000 mg/kg, dermal, rabbit >20 mL/kg skin, sensitizer NEOPENTYL GLYCOL DIGLYCIDYL ETHER 4500 mg/kg, oral rat >2000 mg/kg, dermal, rat Not Available 0.000 TITANIUM DIOXIDE 25000 mg/kg, oral rat Not Available Not Available Not Available

Additional Information:

No Information

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):	No information available.
IC50 72hr (Algae):	No information available.
LC50 96hr (fish):	No information available.

12.2 Persistence and degradability:		No info	ormation available.			
12.3 Bioaccumulative potential:		No info	ormation available.			
12.4 Mobility in soil:		No info	No information available.			
12.5 Results of PBT and vPvB assessment:		The pr	oduct does not meet the	e criteria for PBT/VPvB	in accordance with Annex XIII.	
12.6 Other adverse effects:		No info	ormation available.			
CAS-	<u>No.</u>	Chemical Name		<u>EC50 48hr</u>	IC50 72hr	<u>LC50 96hr</u>
25068	8-38-6	BISPHENOL A EPOXY RESIN		2.1 mg/l (daphnia)	11 mg/l (algae)	1.3 mg/l (fish)
17557	7-23-2	NEOPENTYL GLYCOL DIGLYCIDYL E	THER	No information	No information	No information
13463	3-67-7	TITANIUM DIOXIDE		No information	No information	No information

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

папорон ппоппацон	
UN number	UN3082
UN proper shipping name	Environmentally Hazardous Substance, Liquid, N.O.S.
Technical name	(Epoxy Resin)
Transport hazard class(es)	9
Subsidiary shipping hazard	N/A
Packing group	PGIII
Environmental hazards	Marine Pollutant: Yes (Epoxy Resin)
Special precautions for user	No information available.
EmS-No.:	F-A, S-F
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	No information available.
	UN number UN proper shipping name Technical name Transport hazard class(es) Subsidiary shipping hazard Packing group Environmental hazards Special precautions for user EmS-No.: Transport in bulk according to Annex II

15. Regulatory Information

^{15.1} Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Serious eye damage or eye irritation

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No SARA 313 substances exist in this product above de minimis concentrations.

Toxic Substances Control Act:

All components of this product are either listed on the TSCA Inventory or are exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical Name	CAS-No.
ALUMINUM HYDROXIDE	21645-51-2
Pennsylvania Right-To-Know	

The following non-hazardous ingredients are present in the product at greater than 3%.

No PA Right-To-Know components exist in this product.

CALIFORNIA PROPOSITION 65

WARNING: Cancer and Reproductive Harm -- www.P65Warnings.ca.gov

International Regulations: As follows -

* Canadian DSL:

No Information

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

Reasons for revision

No Information

The information contained herein is, to the best of our knowledge and belief accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.